




# STYLE BETON

## POLYSTYLE

<b>DESCRIPTION</b>	<p><b>Polystyle</b> is a one component water based acrylic polymer. When diluted with water it produces a solution for improving cementitious mixes.</p> <ul style="list-style-type: none"> <li>• Reduced permeability.</li> <li>• Water based.</li> <li>• Improved resistance to freeze.</li> <li>• Just add water.</li> <li>• Improved workability.</li> <li>• Solvent free.</li> <li>• Chloride free.</li> <li>• Non flammable.</li> <li>• Reduced shrinkage and cracking.</li> <li>• Non toxic.</li> </ul>
<b>Colors</b>  <b>Restrictions</b>    <b>Packaging</b>  <b>Storage</b>	<p>White/Liquid</p> <p>In accordance with concrete temperature standards. 5°C-30°C.</p> <ul style="list-style-type: none"> <li>• Polystyle must be diluted with water and mixed with cement .</li> <li>• Apply only to prepared, sound substrates.</li> <li>• Due allowance must be made for the moisture content of the sand to ensure the correct quantity of Polystyle is used as given in the standard mixes. In some circumstances this will result in the addition of undiluted Polystyle to the mix.</li> <li>• Protect freshly applied material from freezing.</li> <li>• Do not add water over recommended dosage.</li> </ul> <p>20 L</p> <p>At room temperature, in the original container.</p>
<b>Application</b>	<p>The prepared substrate should be cleaned with clean water, leaving no standing water. Always apply mix wet on wet onto bonding coat. Re-apply if surface dries.</p>

	<p><b>Use</b></p> <p>Bonding coat</p> <p>Finish Coat</p> <p>- Style Overlay Concrete and Style Stencil Spray.</p> <p style="text-align: right;"><b>Gauging Solution</b> Polystyle : water litres 1 : 1  1 : 3</p>
<b>CLEANING</b>	The tools are recommended to be cleaned immediately after use with water.
<b>HEALTH AND SAFETY</b>	Read the label before use.
<b>GENERAL INFORMATION</b>	<p>Note that the technical application and the experience of work teams will affect the final aesthetic result of the floor.</p> <p>The information and in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual application conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.</p> <div style="text-align: center;">  </div> <p style="text-align: center;"><b>STYLE BETON</b></p> <p style="text-align: center;"><b>Terma Aisopou, Kalochori, Thessaloniki, Greece, 54628</b>  <b>TEL. : 0030 2310 - 920831, FAX : 0030 2310 - 920832,</b>  <a href="http://www.stylebeton.com">www.stylebeton.com</a> , <a href="mailto:info@stylebeton.com">info@stylebeton.com</a></p>