



DECOCHROM

WAX DISPERSION

DESCRIPTION	Water based wax dispersion for optical decoration and to protect rustical plaster surfaces.
Solid	Min: 29,0 % Max: 31,5 % Wax compination
Solvent	Water
Emulsifier-system	Non - ionic
pH-Value	Min: 8,3 Max: 9,3
Density	Min: 1,05 g/ccm Max: 1,07 g/ccm
Viscosity	typ: 31 mPa.s
Packaging	The product is provided in containers weighing 1kg-3kg-13-kg.
Storage	In original closed containers lasting at least 6 months at temperatures between 5-35C. Stir well before use. Protect from frost. After long storage, particularly after usage of some of the product, evaporation of water is possible and visible signs of particles may be present. We therefore recommend filtration of the product before use.
APPLICATION	The DECOCHROM , waterproof and indelible color, protects the surface of the plaster and is available in 7 basic colors. It is applied using sponge, brushes or special paint tool.
CLEANING	The tools are cleaned immediately after application with WATER .

<p>TRANSPORT INFORMATION</p>	<p>No dangerous goods according to international transport regulations.</p>
<p>HEALTH AND SAFETY</p>	<p>GENERAL</p> <p>Immediately remove all contaminated clothing.</p> <p>AFTER SKIN CONTACT</p> <p>Wash away with soap and water and rinse.</p> <p>AFTER EYE CONTACT</p> <p>Remove contact lenses, keep eyelids open. Flush with plenty of water (10-10min.). Call a physician.</p> <p>AFTER INGESTION</p> <p>Rinse mouth with water. If symptoms persist, consult a physician. Drink plenty of water.</p>
<p>GENERAL INFORMATION</p>	<p>Waterproofing, colouring and protective product we can use on the DECOCREATE . Can be provided in a neutral color or in different colors that can be mixed to obtain nuances and wished chromatic effect. The product is provided in containers weighing 0.500kg-3kg-13-kg. Outcomes about 15-20 sq.m. per kg.</p> <p>The information in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that</p>

no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.



STYLE BETON

TERMA AISOPOU, KALOCHORI, THESSALONIKI, 54628
TEL. : 2310 - 920831, FAX : 2310 - 920832,
www.stylebeton.com , info@stylebeton.com